

COMMANDER i ISOBUS compatible

Plug and spray



ISOBUS

COMMANDER i ISOBUS compatible following ISO 11783



ISOBUS ISO 11783

The primary goal of ISOBUS data technology is to standardize the communication which takes place between tractors and implements.

The future aim of the ISOBUS is to achieve a plug and play capability for every combination. Just plug it in, and you are ready to go. One single ISOBUS terminal replaces a multitude of terminals specifically made for single machines combined with the tractor.

ISOBUS bridge

HARDI COMMANDER i sprayers can be ordered with an ISOBUS bridge. By this, the sprayer can be directly operated by means of a virtual ISOBUS terminal.

All intelligent functions such as AutoWash and Prime-Flow, will be operated and controlled from the ISOBUS terminal. To ease operation, the proven HARDI GRIP will be delivered with the COMMANDER i sprayer.

All primary spray functions, such as ON/OFF and section switches as well as the hydraulic operation, can easily and safely be done with the joystick. All secondary functions such as TWIN air assistance, SafeTrack etc. will be operated from the SetBox which is also delivered.

Integrated functions

If the existing virtual ISOBUS terminal has an automatic section control following the defined task controller function of the ISOBUS standard, for example the John Deere Sprayer Pro, the ISOBUS terminal can operate the distribution valves of the COMMANDER, so a separate HARDI AutoSectionControl is not needed.

Data transfer

HARDI sprayers with ISOBUS use the data transfer capabilities of the ISOBUS terminal's task controller. HARDI ISOBUS supplies the data that leading farm software systems require.

Updating

All HC 6500 sprayers can be changed to ISOBUS by adding the HARDI ISOBUS bridge. Sprayers shipped prior to 2010 also need exchange of the GRIP and SetBox. The JobCom only needs a software update.

Use of HC 6500 controller

It is also possible to change a COMMANDER i ISOBUS sprayer to a COMMANDER i HC 6500 version. For this, a HC 6500 display and a HARDI power harness are needed.

HARDI INTERNATIONAL A/s

Helgeshøj Allé 38 • DK 2630 • Taastrup • Denmark
E-Mail: hardi@hardi-international.com • www.hardi-international.com

HARDI Ltd.

Watling suite (unit B)
High cross business park
Coventry road • Sharnford
Leicestershire • LE10 3PG
☎ 01 455 222230 • Fax: 01 455 222240
E-mail: sales@hardi-uk.com • www.hardi.co.uk

Read more at www.hardi-international.com

HARDI - Your Sprayer Specialist

*HARDI reserves the right to change the specifications without notice.
Illustrations shown may include optional extras and accessories.*

