

Powerful & Versatile

Optimum air distribution



CANNON



ZENIT

The HARDI CANNON adapts to any crop type, providing optimum air distribution and maximum air volume. The individual combinations of the three different spouts and the two turbines provide the Versatility and Power so sought after in today's farming.

All the CANNON spouts can be fitted to both the lift mounted ZENIT range and the trailed ARROW and MERCURY sprayers – tank sizes available from 400 to 4000 litres.



Canon Spouts	L	T	M	H	J
ZENIT	X	X	X	X (1000 y 1200 l)	X
MERCURY	X	X	X	X	X
Turbine	P540	P540-D	P540-D	P540-D	P540-D
Air volume, (1.000 m ³ /h)	11	19	19	19	19
Power consumption, (kW)	28	54	54	54	54
Turbine diameter, (mm)	540 single	540 double	540 double	540 double	540 double
Two speed gear box	X	X	X	n	X
Vertical hydraulic adjustments	-10° a + 80°	-10° a + 80°	-10° a + 80°	till 60°	-10° a + 80°
Horizontal hydraulic adjustments	180°	180°	180°	-	180°
Nozzle body	4 BI-JET + 3 adjustable	7 TRI-JET + 3 adjustable	10+3+3 Single	9 TRI-JET + 3 adjustable	7 TRI-JET + 3 adjustable
Spraying height	15 m	20 m	12 m	20 m	30 m
Spraying distance	20 m	+30 m	+20 m	+35 m	+30 m

L Medium size forest, urban trees and horticulture

T Walnuts, avocados and other tall trees incl. urban trees

M Christmas trees, berry bushes, nurseries and other low dense crop

H Horticulture low crop fields green house

J Top spraying tall crops, as banana



HARDI INTERNATIONAL A/s

Helgeshøj Allé 38 • DK 2630 • Taastrup • Denmark
E-Mail: hardi@hardi-international.com • www.hardi-international.com

HARDI reserves the right to change specifications without notice. Illustrations shown may include optional equipment and accessories.



Cert no. SW-COC-00327
www.fsc.org
©1996 Forest Stewardship Council

HIA MARKETING
GB-850711-12-0010