

HARDI PUMP 603



General specifications

- Compact two diaphragm positive displacement pump.
- Low power consumption.
- Self-priming.
- Can be run dry.
- Can rotate clockwise or anticlockwise.
- Single grease point for lubrication.
- Dry sump to simplify maintenance.
- No special tools needed for maintenance.
- Polyurethane diaphragms and seals.
- Cast iron crankcase and covers.
- 3/4" suction port, 3/4" pressure port.
- Recommended to use HARDI suction and pressure dampers.

603/4.0 (Ref. no. 821625)

- Cylindrical shaft, 25 mm / 0.98".
- For combustion and electric engine use.
- Supplied with narrow base plate.
- Normal operating revolutions, 800 r/min.
- Maximum pressure, 15 bar / 220 PSI.
- Maximum vacuum, 0.85 bar / 12.5 PSI.
- Weight, 14.8 kg / 33 lb.

603/7.0 (Ref. no. 821624)

- Tapered shaft.
- For tractor use with HARDI transmission shaft.
- Supplied with wide base plate.
- Normal operating revolutions, 540 r/min.
- Maximum pressure, 15 bar / 220 PSI.
- Maximum vacuum, 0.91 bar / 13.4 PSI.
- Weight, 15.4 kg / 34 lb.

603/7.0 (Ref. no. 821623)

- Tapered shaft.
- With 6-splined coupling for tractor P.T.O. shaft.
- Normal operating revolutions, 540 r/min.
- Maximum pressure, 15 bar / 220 PSI.
- Maximum vacuum, 0.91 bar / 13.4 PSI.
- Weight: 16.2 kg / 36 lb.



603/7.0 on an industrial cleaner



603/7.0 with PTO coupling

